

**TECHNICAL
INFORMATION**

In the interest of continuing product improvement, we reserve the right to change models, specifications, and/or features without prejudice.

PROJECT: _____
 LOCATION: _____
 ARCHITECT: _____
 ENGINEER: _____
 CONTRACTOR: _____
 DATE: _____ SALES ENGINEER: _____

Direct Mount to Arm - D-Series

Blower mounted to arm wall bracket.

The blower can be rotated 360 degrees in 90 degree increments. This allows for discharge for a variety of requirements.



Internal Support Models

<u>Single Phase</u>	<u>Three Phase</u>
D075-SS-1-DMA	D075-SS-3-DMA
D10-SS-1-DMA	D10-SS-3-DMA
D15-LS-1-DMA	D15-LS-3-DMA
D20-LM-1-DMA	D20-LM-3-DMA
D30-LM-1-DMA	D30-LM-3-DMA

Tube Type Models

<u>Single Phase</u>	<u>Three Phase</u>
D075-SS-1-DMA	D075-SS-3-DMA
D10-SS-1-DMA	D10-SS-3-DMA
D15-LS-1-DMA	D15-LS-3-DMA
D20-LM-1-DMA	D20-LM-3-DMA
D30-LM-1-DMA	D30-LM-3-DMA

