



Direct Drive Fans  
Blower Performance  
D Series

## TECHNICAL INFORMATION

In the interest of continuing product improvement,  
we reserve the right to change models,  
specifications, and/or features without prejudice.

PROJECT: \_\_\_\_\_  
LOCATION: \_\_\_\_\_  
ARCHITECT: \_\_\_\_\_  
ENGINEER: \_\_\_\_\_  
CONTRACTOR: \_\_\_\_\_  
DATE: \_\_\_\_\_ SALES ENGINEER: \_\_\_\_\_

www.monoxivent.com

info@monoxivent.com

309-794-1000

Page: EF-4

### BLOWER PERFORMANCE CFM RATINGS AT LISTED SP

Model	HP									DBA at
		1"	2"	3"	4"	5"	6"	7"	5'	
D05-SS	0.5	450	435	390	350	260	150	---	---	85
D075-SS	0.75	475	430	365	330	240	---	---	---	83
D10-SS	1.0	---	---	---	770	665	540	320	---	83
D15-LS	1.5	965	910	840	780	675	550	330	---	83
D20-LM	2.0	---	---	1237	1140	1070	990	915	---	86
D30-LM	3.0	1490	1420	1275	1213	1140	1070	990	---	86

\* **Note: Standard Motors are Baldor with TEFC Enclosure. Motor - 3450 RPM. Standard Motors are UL UR**  
Recognized as a component and CSA Certified in Canada.

The D Series Fans are not UL Listed or CSA Certified as an assembly.

Motor specifications subject to change without notice.

The construction is Silumin (Silicon Aluminum Alloy) for the housing and the wheel.

--- = Unstable operation

**1 Phase:**  
**115/208/230 Volt**

**3 Phase:**  
**208/230/460/575 Volt**