



Direct Drive Fans
Blower Performance
D Series

TECHNICAL INFORMATION

In the interest of continuing product improvement,
we reserve the right to change models,
specifications, and/or features without prejudice.

PROJECT: _____
LOCATION: _____
ARCHITECT: _____
ENGINEER: _____
CONTRACTOR: _____
DATE: _____ SALES ENGINEER: _____

www.monoxivent.com

info@monoxivent.com

309-794-1000

Page: HRSO-11

BLOWER PERFORMANCE CFM RATINGS AT LISTED SP

| Model | Weights | HP | 1" | 2" | 3" | 4" | 5" | 6" | 7" | 8" | 9" | DBA at 5' |
|-------|---------|-----|------|------|------|------|------|------|-----|-----|-----|--------------|
| D05 | 75 lbs. | .5 | 450 | 435 | 390 | 350 | 260 | 150 | --- | --- | --- | 85 |
| D10 | 75 lbs. | 1.0 | --- | --- | --- | 770 | 665 | 540 | 320 | --- | --- | 83 |
| D15 | 75 lbs. | 1.5 | 965 | 910 | 840 | 780 | 675 | 550 | 330 | --- | --- | 83 |
| D20 | 75 lbs. | 2.0 | -- | --- | 1237 | 1140 | 1070 | 990 | 915 | 825 | 735 | 86 |
| D30 | 80 lbs. | 3.0 | 1490 | 1420 | 1275 | 1213 | 1140 | 1070 | 990 | 915 | 825 | 86 |

* **Note:** Standard Motors are Baldor with TEFC Enclosure. Motor - 3450 RPM. Standard Motors are UL UR Recognized as a component and CSA Certified in Canada.

The D Series Fans are not UL Listed or CSA Certified as an assembly.

Motor specifications subject to change without notice.

The construction is Silumin (Silicon Aluminum Alloy) for the housing and the wheel.

--- = Unstable operation

1 Phase:
115/208/230 Volt

3 Phase:
208/230/460/575 Volt