

Series 7120 External Helix Hose For Temperatures Up to 1200°F



In the interest of continuing product improvement, we reserve the right to change models, specifications, and/or features without prejudice.

info@monoxivent.com

PROJECT:	
LOCATION:	
ARCHITECT:	
ENGINEER:	
CONTRACTOR:	
DATE:	SALES ENGINEER:

Page: HS-13

www.monoxivent.com

EXTERNAL HELIX HOSE FOR TEMPERATURES UP TO 1200°F



SERIES 7120

Material

Hose wall double layer:

Inner wall: heat resistant impregnated glass fabric Outer wall: special coated high temperature fabric, asbestos free, reinforced by woven in stainless steel wire External helix: galvanized steel

Applications

- Exhaust fume extraction from Shipbuilding industry high performance test beds in • Defense industry the motor vehicle industries
- Diesel exhaust
- Automotive manufacturing
- Aircraft manufacturing
- Shipbuilding industry

Properties

- Flame-resistant
- · Very high temperature resistance
- Silicone-free
- Highly flexible
- Extreme compressibility 1:6
- Small bend radius
- · External steel helix protects against abrasion
- Suitable for continually flexing
- Special clamping method guarantees high tensile strength between hose material and external helix
- · To maximize life of duct and exhaust system effectiveness, it is recommended to utilize a negative pressure exhaust system and introduce ambient air at the inlet.

* Larger sizes available, consult factory for pricing.

Construction

1. External helix

309-794-1000

- 2. Outer wall: special coated high temperature fabric
- 3. Inner wall: heat resistant fabric



Temperature Range*

- -5°F up to +1200°F
- Intermittent to +1300°F
- · Small amounts of smoke may be given off when used under positive pressure or with low extraction rates.

*Hoses used for vehicle exhaust extraction, or operating near maximum temperature, must be used within a properly designed fan system to avoid damaging the hose.

Dia (in.)	Positive (in. w.c.)	Negative (in. w.c.)	*Bending radius (in.)	Weight (lbs./ft.)
3.00	201	102	1.80	0.83
4.00	141	67	2.40	1.07
5.00	109	42	3.00	1.33
6.00	69	30	3.60	1.58
8.00	49	17	4.80	2.10
10.00	39	12	7.00	2.63
12.00	33	8	8.40	3.16
14.00	20	6	9.80	3.67
16.00	16	4	11.20	4.26
18.00	12	4	14.40	4.94

* Referring to the inner side of the elbow of hose

The above mentioned data refers to an average and ambient temperature of 68°F. Subject to technical changes and color variations

General engineering Suction plants

- Radiant heat protection
- Primarily suited as
 - extraction hose