

Source Capture Arms External Support Structure Series 15000-EXT (7')

## TECHNICAL INFORMATION

In the interest of continuing product improvement, we reserve the right to change models, specifications, and/or features without prejudice.

PROJECT:	
LOCATION:	
ARCHITECT:	
ENGINEER:	
CONTRACTOR:	
DATE:	SALES ENGINEER:

Page: WSC-14B

www.monoxivent.com

info@monoxivent.com

309-794-1000

15000-EXT (7') 5-1/2" 3-1/8" <sup>1</sup>/2" Holes (x3) 120 80 40 Working radius Max. radius \*At a mounting height of 6 feet, and a working height of 2 feet, 6 inches. \*\*At a mounting height of 7 feet, and a working height of 2 feet, 6 inches. Model **Work Radius Max Radius** 15074-EXT 37.5" 19" 57"\* 80" 15075-EXT 37.5" 19" 57"\* 80" 19" 57"\* 80" 37.5" 15076-EXT 37.5" 19" 57"\* 80" 15078-EXT \* At a mounting height of 7 feet amd a working height of 30 inches.

Nozzle: Injection molded in with hood plate in anodized aluminum.

**Hose:** Hose of dark-blue PE-coated polyamide fabric rated to 215 degrees F.

Other options available (chemical & abrasion resistant) - please consult factory

Optional light kit or fan/damper switch available.